

Product: KLUDI BALANCE electronic controlled basin mixer DN 10

Ref.: 5220205

Product description

electronic controlled basin mixer DN 10
 single hole mounted
 flow rate 5,0 l/min
 flow straightener M 24 x I with anti-theft device
 magnet-cartridge unit, with presettable temperature control handle
 optical object-registration
 electronic unit with control device
 electric power supply via 230 V main adapter
 rapid installation set
 flexible high pressure supply tubes G 3/8 with dirt catcher sieve
 noise group I, protected against vandalism
 for use with displacement heaters

Finishes:
 05 chrome



Advertisement

- * KLUDI GmbH & Co KG KLUDI BALANCE electronic controlled basin mixer item no. 5220205 DN 10
- ** electric power supply via 230 V main adapter
- *** temperature control handle
- **** chrome plated brass, DIN 50930-6, ajar to DIN EN 15091

Electronic controlled basin mixer DN 10, manufacturer KLUDI GmbH & Co KG KLUDI BALANCE item no. 5220205, DN 10, chrome plated brass DIN 50930-6, as electronic controlled pillar tap, according to technical requirements DIN EN 15091 and VDE 0630 part 12/09.88, electronic = electromagnetic compatibility proofed, flexible high pressure supply tubes length 350/500 mm with metal body 3/8 inch with DVGW / KIWA / WRAS / CSTB approval (W543/W270), noise level DIN 4109 group I, without report no., flow straightener M 24 x I with anti-theft device, control electronic with programming options, activation optoelectronic, with electric power supply via 230 V main adapter, safety class IP 65, with presettable temperature control handle, flow rate 5,0 l/min, max. warm water intake temperature 65 °C (as scald protection), with activatable/deactivatable 24 h automatic flush, with functional reliability magnet-cartridge unit, protected against vandalism, with integrated sensory window, valve closed in rest position, rapid installation system, projection in mm 129, spout height in mm 106/129,5, total height in mm 129,5, with adjustable water run-time (0,1 – 5 sec.), with 2 minutes short-off function, with (set/free adjustable) hot water safety device via mixing shaft, for use with displacement heaters, PN 0,

